

Ramsay Ladders



61 West High Street
Forfar
Town of Forfar, Angus DD8 1BG
United Kingdom

Phone: 01307462255
Fax: 01307466956

Ramsay Ladders Welcome to Ramsay Ladders. This editorial contains our main range of Ladders and Stepladders, if you have need for a product not shown here then please contact our Sales Department who will be glad to help. Safety is a prime concern for us at Ramsay Ladders. The range of products available to you is as diverse as the purposes for which they are used. Ramsay Ladders cover a broad spectrum of commercial and industrial uses, regardless of its purpose or the environment in which it is to be used, every ladder is designed with the latest innovations and manufactured to a standard that few companies can match. In the event that we don't have a standard ladder to suit your needs, our Ramsay Access Division will design and manufacture to your individual needs. Like Ramsay Ladders this division places great emphasis on the consistently high quality of our products, all being designed to meet current regulations regarding health and safety. Single Section Ladders Ladders manufactured from hollow seamless aluminium extrusions with radiused corners for extra strength. Sizes vary in depth and width according to size of ladder. Rungs either 24mm or 30mm diameter serrated tube fitted through stiles at a standard rise of 250mm by a special locking method to prevent turning and for increased strength. Ends of ladder stiles fitted with rubber plugs. Special Single Section Ladders can be manufactured to customers own requirements ie:- Different lengths, rung spacing and width (maximum 810mm). Please enquire to our

Sales Department for details. Double Extension Ladders Ladders manufactured from hollow seamless aluminium extrusions with radiused corners for extra strength. Sizes vary in depth and width according to size of ladder. Rungs either 24mm or 30mm diameter serrated tube fitted through stiles at a standard rise of 250mm by a special locking method to prevent turning and for increased strength. Ends of ladder stiles fitted with rubber plugs. Rope operation can be fitted to ladders with the reference letters L-E-F-J at extra cost. Rope operated ladders have a special type of swing clutch complete with side operated ropes and pulleys. Rope operation CANNOT be fitted afterwards to push-up extension ladders. Preference for rope operation must be stated when ordering Triple Extension Ladders Ladders manufactured from hollow seamless aluminium extrusions with radiused corners for extra strength. Sizes vary in depth and width according to size of ladder. Rungs either 24mm or 30mm diameter serrated tube fitted through stiles at a standard rise of 250mm by a special locking method to prevent turning and for increased strength. Ends of ladder stiles fitted with rubber plugs. Rope operation can be fitted to ladders with the reference letters D and F at extra cost. Rope operated ladders have a special type of swing clutch complete with side operated ropes and pulleys. Rope operation CANNOT be fitted afterwards to push-up extension ladders. Preference for rope operation must be stated when ordering. Combination Ladders This ladder can be used as a Double Extension Ladder with splayed base, or a Step Ladder or as two Single Section Ladders. Manufactured from hollow seamless aluminium extrusions with radiused corners for extra strength. Rungs of 24mm diameter serrated tube fitted through the stiles at a standard rise of 250mm by a special locking method to prevent turning and for increased strength. Ends of ladder stiles fitted with rubber feet. Window Cleaning Ladders - Single Section These ladders are produced for the Window Cleaning trade, having a pointed top fitted with white rubber block (105mm wide) and a tapered/splayed base. Manufactured from hollow seamless aluminium extrusions with radiused corners for extra strength. Rungs of 24mm diameter serrated tube fitted through stiles at a rise of 250mm by a special locking method to prevent turning and for increased strength.

Ends of ladder stiles fitted with rubber plugs. Roof Ladders Ladders manufactured from Single Section models (SA). Fitted with tubular steel ridge hook complete with runner wheels, also fitted with rubber covered supports on the underside. Ends of ladder stiles fitted with rubber plugs. Extensions manufactured from Single Section models (SA). Fitted with sleeved joining plates and rubber covered supports on underside. NOTE: When ordering please indicate Roof Ladder Type 'K' or 'L'. Double Extension Roof Ladders also available ask our sales department for details. Surveyors Ladders Ideal for inspection purposes, this ladder can be easily carried and stored in the boot of a car. Manufactured from hollow seamless extrusions with radiused corners for extra strength. Rungs of 24mm diameter serrated tubing fitted at a standard rise of 229mm by a special locking method to prevent turning and for increased strength. Overall width 323mm. Ends of ladder stiles fitted with rubber plugs. Folding Platform Steps - Heavy Duty Manufactured from heavy duty aluminium channels fitted with 89mm deep treads fitted at a standard rise of 254mm. Hinged to a back 'A' frame angle section. Bottom ends of stiles fitted with rubber plugs. Platform size 406mm long x 305mm wide. Swingback Steps - Standard Manufactured from aluminium channels fitted with 80mm deep treads fitted at a standard rise of 254mm. Hinged to a back 'A' frame angle section. Bottom ends fitted with rubber feet. These steps can be fitted with a Fixed or Collapsible Handrail at top; Tool Tray/Bucket Rest and/or side Handrails. Double Sided Steps Manufactured from aluminium channels fitted with 89mm deep treads fitted at a standard rise of 254mm. Bottom ends fitted with rubber plugs. Fixed Platform Steps - Double Sided Manufactured from aluminium channels fitted with 89mm deep treads fitted at a standard rise of 254mm. Bottom of channels fitted with rubber plugs. Platform of 5-bar treadplate and measures 610mm deep x 380mm wide. Mobile Warehouse Steps Manufactured from heavy duty aluminium channels, fitted with 89mm deep treads at a standard rise of 254mm. Platform measures 530mm deep x 400mm wide. Handrails fitted to both sides (supplied loose). 125mm dia. wheels fitted to rear for easy movement. These steps can be supplied in easy to assemble 'knock down' form if required at extra cost. Mobile

Steel Platform Steps • Tubular Steel all welded construction.

- Retractable Castors at front and Fixed Wheels at rear.
- Locking Handle for immobilising Steps and Castors when in use, which is also the

Climbing Restraint when not in use.

- Platform 550mm wide x 375mm deep fitted with a 150mm Toeboard.
- Treads 550mm wide x 195mm deep. Treads can either be Punched Steel or Anti-

Slip.

- Can be manufactured to fold when not in use (extra cost).
- Painted finish either Blue or Red. National Grid Ladders

Ladders manufactured from hollow aluminium rectangular sections with radiused corners for extra

strength. Rungs of 30mm dia. corrugated tube fitted through the stiles at a

standard rise of 250mm by a special locking method to prevent turning and for

increased strength. Overall width of ladder 355mm. Ends of ladders fitted with

rubber plugs. Some of the Services we Offer Include: Ladders Forfar • Step Ladders

Forfar • Platforms Forfar • Loft Ladders Forfar • Football Goal Frames Forfar •

Extensions Ladders Forfar • Mobile Warehouse Steps Forfar • Glass Fibre Ladders •

Timber Ladders • Extension Ladders • Mobile Warehouse Steps

[Visit Website](#)

[Send Message](#)

[Email Friend](#)